

### DISPERSION

# PERFEKTA

Acrylic paint for walls and ceilings



### MAIN ADVANTAGES

- High coverage
- High resistance to washing and scrubbing
- For mineral and painted substrates
- Pleasant painting experience
- Perfect result
- Wide range of colours

### AREAS OF APPLICATIONS

The dispersion topcoat paint for interiors is intended for performing paint coatings characterised by pleasant matt optics. It is especially recommended for primary and renovation painting of walls and ceilings in 'dry' rooms (such as living rooms, bedrooms, halls and office rooms and conference halls). It may be used both for painting substrates of uniform and changeable structure and colour. It is designed for painting of all typical mineral substrates (such as concrete, cement plasters, cement-lime plasters, lime plasters and skim coats and drywalls) and on substrates covered with well set and bound polymer-based coats. Absorbent substrates should be primed with **BUDOGRUNT WG** or **AQUALIT** before paint application.

### TECHNICAL SPECIFICATION

**Base binder:** copolymer binder;  
**Pigments:** titanium dioxide white powder and coloured pigments;  
**The content of volatile organic compounds VOC:** cat. A/a. The product contains less than 30 g / l VOC;  
**Density:** ca. 1.50 g/cm<sup>3</sup>;  
**Colours:** white and colours according to KABE, NCS colour scheme or according to samples provided;  
**Gloss level:** matt;  
**Diluent:** water;  
**Average coverage:** ca. 0.25 l/m<sup>2</sup> (with double painting on a smooth substrate);  
**Temperature of application (air and substrate):** from +5°C to +25°C;

**Relative humidity:** ≤80%  
**Resistance to wet scrubbing:** paint of class II (per PN-EN 13300 standard) and paint of class I (per PN-C-81914: 2002 standard).  
**Packaging:** Single-use plastic packaging containing 3, 5, 10 and 15l of product.  
**Storage:** The product should be stored in its sealed packaging in a cool, but frost-protected room. Keep out of the reach of children.  
**Shelf life:** Originally sealed products have a 18-month shelf life from the date of production (this is printed on the side of the packaging).

### APPLICATION METHOD

**SUBSTRATE PREPARATION:** Apply to a sound/stable and clean substrate (without cracks and delaminations), degreased, dry, and free of biological contamination or chemical efflorescence. In the case of fungal growth, the substrate should be mechanically cleaned and then disinfected with an indoor fungicide. Discolourations, nicotine stains and efflorescences caused by water stains should be painted first with **MILAMAT** stain blocker. Any loose layers not bound to the substrate (i.e. loose render or flaked coatings) should be removed. The remnants of adhesive or lime paints should be thoroughly removed and the substrate washed with water. Old and/or dirty substrates should be washed off and degreased with water and **CLEANFORCE** cleaning agent. For uneven substrates, first use levelling compound and then level the surface with **PROFINISZ** ready-to-use finishing compound. Small unevenness can be levelled out at once with **PROFINISZ** ready-to-use finishing compound. Use the above products according to their technical data sheets. Absorbent substrates should be primed with **BUDOGRUNT WG** before ready-to-use finishing compound and/or levelling compound application. Fresh cement plasters and cement-lime plasters may be painted after 3-4 weeks of curing period, gypsum plasters after 2 weeks, while the so-called drywall construction can be painted directly after polishing and dust removing.

**PRIMING:** Prior to paint application, absorbent or dusty (strongly chalking) substrates should be primed with **BUDOGRUNT WG**. Gypsum substrates or non-uniform ones should be primed with **AQUALIT**. Typical drying time ca. 3 h for the product or base applied on the substrate in optimum conditions (20°C, 55% RH). When primer or base applied on the substrate is completely dry, **PERFEKTA** paint may be applied. **Note:** Substrates of low wettability (such as top coats based on polymers or dispersion paint coatings) should not be primed and only washed with water with the addition of **CLEANFORCE** cleaning agent.

**PAINT PREPARATION:** If required, add a small amount of clean water adding 10% of volume for the first painting and 5% for the second one (when determining the amount of water, it is necessary to take into account the type of substrate, drying conditions and application technique).

**APPLICATION:** Paint should be applied on the substrate in two layers with a brush, roller or by spraying (including also the 'airless' method). It is recommended to use a fleece paint roller with a bristle length of 18 mm. The second coat can be applied only after the first one is completely dry.

Spraying parameters for an airless type device:

Manufacturer	Device	Nozzle	Pressure [bar]	Filter [mesh]	Dilution [%]	Usage [kg/min]
WAGNER	ProSpray 3.21	0552-517	200	60	5÷15	1.25
TITAN	Titan 450e	661-517	200	60	10	1.25
GRACO	St Max 495	PAA517	180	60	5	2.3

**DRYING:** typical drying time of a single layer of paint applied to the substrate lasts approx. 3 h (20°C, 55% RH) After painting, closed rooms should be aired until the specific smell disappears. **Note:** The drying time may be longer due to low temperatures and high relative humidity. The coating obtains its full mechanical and functional properties after 4 weeks.

**USEFUL HINTS:** To avoid colour differences, a single batch product should be used on a single application / architectural element. Application and drying of the paint requires air temperature above +5°C. All tools to be cleaned with water after finishing work.

If surfaces of disadvantageous lighting are painted, it is recommended to apply **AQUATEX** or **OPTILATEX** or **TOP WHITE ANTI-REFLEX** deep matt paint.

**ADDITIONAL OPTIONS:** When applying the paint on substrates with scratches up to 0.3 mm wide (such as shrinkage cracks in mineral plaster), it is recommended to use a microfiber-reinforced paint for the first painting (option available on order). In order to increase the resistance of the paint coating to mould growth, it is recommended to apply a special protective agent to the paint (additional service).